

MATERIAL (ROHS COMPLIANT):

1. CABLE: UL1007 18AWG, OD:2.1MM COLOR: YELLOW X 1PC, BLACK X 2PCS, RED X 1PC

2. CONNECTOR :

SERIAL ATA 15P MALE, GOLD PLATED CONTACT


OVERMOLD: PVC 50P COLOR BLACK

3. CONNECTOR :

TERMINAL: 4PIN MALE 5.08" PITCH TIN-PLATED

HOUSING: 4PIN FEMALE 5.08" PITCH WHITE COLOR INSULATION

4. L = 220+/- 10MM



P1	P2
1 YELLOW	1 (1, 2, 3)
2 BLACK	2 (4, 5, 6)
3 BLACK	4 (10, 11, 12)
4 RED	3 (7, 8, 9)

ELECTRICAL:

1. CONTACT RESISTANCE: 5 OHM (MAX.)

2. 100% OPEN, SHORT AND MIS-WIRING TEST

3. INSULATION RESISTANCE: 10 M OHM

Itemref	Quantity	Title/Name, designation, material, dimension etc			Article No./Reference	
Designed by	Checked by	Approved by - date JAN.20,2011	File name POWER CABLE	Date JAN.20,2011	Scale FREE	
			4PIN / SATA 15			
			26-1002RM	Edition 1	Sheet 1/1	